

SURFACE WEATHER OBSERVATIONS

(Rev. 1-1-55)

STATION Cobinth, Miss. (SAURS) DATE JUNE 21, 1961

TYPE	TIME (LST)	SKY and CEILING (Hundreds of Feet)	VISIB- ILITY (Miles)	WEATHER and OBSTRUCTIONS TO VISION	SEA LEVEL PRESS. (mbs.)	TEMP. (°F)	DEW PT. (°F)	DIREC- TION	WIND SPEED (kts)	CHARAC- TER AND SHIFTS	ALTIM- ETER SET. (ins.)	REMARKS AND SUPPLEMENTAL CODED DATA			OBSER- VERS INITIALS	
												13	14A	14B		
RS	0545	E 80/10	7			63	61	↓	3			Thin Spots INOVC	10	62.5	61.0	JH
RS	0645	E 100/15	7			64	60	↓	3				10	63.5	61.5	JH
RS	0745	E 80/10	7			66	61	↓	8			BINOVC	10	65.5	62.5	JH
RS	0845	E 100/15	7			69	61	↓	3+11			BINOVC	10	68.8	63.9	JH
R	0945	E 100/15	7			70	61	↓	8+11				9	69.5	64.0	JH
R	1045	E 100/20	7			71	61	↓	3			BINOVC	10	71.0	64.5	JH
R	1145	E 100/20	7			73	60	↓	8				9	73.0	64.5	JH
R	1245	E 100/15	7			72	61	↓	8				10	72.0	65.0	JH
RS	1345	150 A 250/30	7			73	62	↓	8				10	73.0	66.0	FB
R	1445	150 E 200/25	7	H		72	63	↓	8				10	72.0	66.0	FB
R	1545	E 200/10	7	H		71	64		C				10	71.0	66.5	FB
R	1645	E 250	7	H		71	62		C				10	71.0	65.0	FB
RS	1745	B 180/10	7	H		70	62		C				10	70.0	65.0	FB
S	1820	E 250/10	7			70	62		C			LWR CLDS S	8	70.0	65.0	FB
R	1845	250	7			70	62		C				3	70.0	65.0	FB
R	1945	O	7			65	62		C					65.0	63.0	FB
R	2045	O	7			62	60		C					62.0	61.0	FB
R	2145	O	5	GF		61	60		C			GF DEP 8 FINCRG		60.5	60.0	FB
RS	2245	O	2	GF		59	58		C			FINCRG		58.5	58.0	FB
JUNE 22, 1961																
RS	0545	W 1X	0	F		56	56		C				10	55.5	55.5	JH
RS	0645	W 1X	1/4	F		57	56		C				10	57.0	56.5	JH
RS	0745	W 2X	3/4	F		64	61		C				10	64.0	62.0	JH
S	0815	60	5	F		M	M		C				2	M	M	JH
R	0845	100	7			68	63		C				2	68.0	65.0	JH
R	0945	350	7			73	59	↑	3				2	73.2	64.0	JH
R	1045	350/10	7			72	61		C				3	71.5	64.5	JH
R	1145	350	7			73	60	→	3				2	73.0	64.5	JH
R	1245					M	M					FINO		M	M	JH
R	1345	400/10	7			81	60	↑	3				2	80.5	67.0	JH
R	1445	400	10			82	60		C				1	81.7	67.5	WS
R	1545	400	10			83	62	↑	6				1	83.0	68.8	WS
R	1645	O	12			82	60	→	8					82.4	67.5	WS
R	1745	O	12			81	59	↑	9					81.0	66.7	WS
R	1845	1-10	12			77	62		C				1	77.0	67.3	WS
R	1945	10	12			72	62		C				3	71.7	65.6	WS
R	2045	10	12			70	62		C				2	69.9	64.8	WS
R	2145	10	12			70	60		C				2	70.0	63.8	WS