

SURFACE WEATHER OBSERVATIONS

STATION CORINTH MISS (SAWRS) DATE OCTOBER 21, 1961

TYPE	TIME (LST)	SKY and CEILING (Hundreds of Feet)	VISIB- ILITY (Miles)	WEATHER and OBSTRUCTIONS TO VISION	SEA LEVEL PRESS. (mbs.)	TEMP. (°F)	DEW PT. (°F)	DIREC- TION	WIND SPEED (kts)	CHARAC- TER AND SHIFTS	ALTIM- ETER SET. (ins.)	REMARKS AND SUPPLEMENTAL CODED DATA	OBSER- VERS INITIALS			
1	2	3	4	5	6	7	8	9	10	11	12	13	14A	14B	15	
R	0545	E 20 ⊕	7			49	45	↓	6				10	48.5	46.5	FB
RS	0645	B 15 ⊕	7			49	45	↓	3			BINOV	10	49.0	47.0	FB
R	0745	E 15 ⊕	7			52	46		C				10	52.0	49.0	FB
R	0845	E 15 ⊕	7			53	47	↓	12				10	53.0	50.0	FB
R	0945	E 15 ⊕	7			55	48	↓	5				10	55.0	51.0	FB
R	1045	E 15 ⊕	7			56	48	↓	7				10	56.0	51.5	FB
R	1145	E 15 ⊕	7			58	49	↓	7				10	58.0	53.0	FB
R	1245	B 15 ⊕	7			59	49	↓	10			BINOV	10	59.0	53.5	FB
R	1345	B 15 ⊕	7			60	51	↓	10			BINOV	10	60.0	55.0	FB
RS	1445	400	6	HK		62	50	↓	11				3	62.0	55.0	WS
R	1545	O	7			62	49	↓	4				62.3	54.9	WS	
R	1645	O	7			57	50		C				56.8	52.9	WS	
R	1745	O	7			55	49		C				55.2	51.8	WS	
R	1845	O	7			52	47		C				51.5	49.2	WS	
R	1945	O	7			51	47		C				50.5	48.4	WS	
R	2045	O	7			48	46		C				47.9	46.7	WS	
R	2145	O	7			45	43		C			PATCHES GF LOW AREAS	44.8	44.0	WS	
S	2202	-X	1/2	F				↓	3				8			WS
RS	2245	-X	1	F		42	41		C				6	41.9	41.7	WS
OCTOBER 22, 1961																
RS	0545	W O X	0	F		37	37		C				10	37.0	37.0	FB
RS	0645	W I X	1/4	F		37	36		C				10	37.0	36.5	FB
R	0745	W I X	1/4	F		42	41		C				10	42.0	41.5	FB
RS	0845	W I X	1/2	F		45	43		C				10	45.0	44.0	FB
RS	0945	W 2 X	3/4	F		49	46	↓	3				10	48.5	47.0	FB
RS	1045	W 3 X	1	F		52	48		C				10	52.0	50.0	FB
R	1145	W 3 X	1	F		54	49	↓	5				10	54.0	51.5	FB
RS	1245	-X B 10 ⊕	4	H F		55	49	↓	3				10	54.5	51.5	FB
R	1345	E 10 ⊕	4	H		55	50	↓	5				10	55.0	52.0	FB
R	1445	E 10 ⊕ 15 ⊕	4	H		56	49	↓	10			BINOV	10	56.1	52.4	WS
RS	1545	O	5	H		58	50	↓	4				57.8	53.3	WS	
R	1645	O	6	H		56	50		C				56.3	52.6	WS	
R	1745	O	5	H		52	49		C				51.8	50.0	WS	
RS	1845	O	2	GF		49	47		C				48.6	47.7	WS	
RS	1945	-X	1	GF		46	45		C				5	45.6	45.3	WS
S	2005	-X	1/2	GF					C				8			WS
RS	2045	-X	1/4	GF		43	42		C				8	42.7	42.5	WS
RS	2145	-X	1/8	GF		42	42		C				9	42.4	42.1	WS